



APPLICATIONS

- Dry materials suction and delivery hose specially designed for transfer of dry cement, sand, gravel, feed, seeds etc. by suction, gravity or by pneumatic systems.

TUBE

- Smooth black anti-static inner tube compounded for long wear resistance in handling hard, sharp, abrasive materials.

REINFORCEMENT

- High strength synthetic cord plus embedded steel helix wire and anti-static copper wire.

COVER

- Smooth long lasting wrapped finish synthetic rubber that is wear, weather and ozone resistant.

COLOUR

- Black with green spiral stripe.

TEMPERATURE RANGE

- -40°C (-40°F) to +70°C (+158°F)

WORKING PRESSURE

- 150 PSI / 10 BAR

SAFETY FACTOR

- 3:1

REMARKS

- Abrasion loss of inner tube rubber compound is according to DIN 53516:70±5mm³.
- Available in 300 PSI, BMH300.

I.D Ø		O.D Ø		Working Pressure		BR	Vacuum	Weight	
inch	mm	inch	mm	bar	psi	mm	bar	lbs/ft	kg/m
2	51	2.56	65	10	150	230	0.9	1.39	2.08
3	76	3.63	92	10	150	360	0.9	2.20	3.28
4	102	4.72	120	10	150	515	0.9	3.46	5.15
5	127	5.80	147	10	150	675	0.9	4.54	6.76
6	152	6.97	177	10	150	900	0.8	7.98	11.88

* Other sizes, length, pressure ratings and colors are available on request