



APPLICATIONS

- Mandrel built lightweight softwall hose. Particularly suitable for submersible pumps, irrigation and drainage systems, sewer cleaning, etc. This hose feature a rolled-up flat capability for easy storage.

TUBE

- Smooth black synthetic rubber inner tube.

REINFORCEMENT

- High strength synthetic cord.

COVER

- Smooth long lasting wrapped finish in synthetic rubber that is abrasion, weather and ozone resistant.

COLOUR

- Black

TEMPERATURE RANGE

- 40°C (-40°F) to +100°C (+212°F)

WORKING PRESSURE

- 75 PSI / 5 BAR

SAFETY FACTOR

- ($\leq 254\text{mm}$) 4:1
- ($\geq 305\text{mm}$) 3:1

I.D Ø		O.D Ø		Working Pressure		Weight	
inch	mm	inch	mm	bar	psi	lbs/ft	kg/m
2	51	2.56	57	5	75	0.52	0.77
3	76	3.54	83	5	75	0.82	1.23
4	102	4.09	108	5	75	1.03	1.54
5	127	5.24	133	5	75	1.25	1.86
6	152	6.22	158	5	75	1.49	2.23
8	203	8.39	213	5	75	2.81	4.19
10	254	10.39	264	5	75	4.15	6.20
12	305	12.48	317	5	75	5.09	7.60

• Other sizes, length, pressure ratings and colors are available on request