



APPLICATIONS

- Softwall hose used for delivery of petroleum products with aromatic content up to 30%.

TUBE

- Smooth black nitrile compound.

REINFORCEMENT

- High strength synthetic cord plus antistatic copper wire.

COVER

- Smooth long lasting wrapped finish high grade chloroprene rubber especially compounded for resistance to weather, ozone, abrasion and oil.

COLOUR

- Black with red spiral stripe.

TEMPERATURE RANGE

- -15°C (+5°F) to +70°C (+158°F)

WORKING PRESSURE

- 150 PSI / 10 BAR

SAFETY FACTOR

- 4:1

I.D Ø		O.D Ø		Working Pressure		Weight	
inch	mm	inch	mm	bar	psi	lbs/ft	kg/m
1	25	1.42	36	10	150	0.46	0.69
1-1/4	32	1.65	42	10	150	0.64	0.96
1-1/2	38	2.05	52	10	150	0.86	1.29
2	51	2.52	64	10	150	0.96	1.43
2-1/2	63.5	3.11	79.5	10	150	1.47	2.19
3	76	3.54	90	10	150	1.49	2.23
3-1/2	90	4.13	105	10	150	1.93	2.88
4	102	4.65	118	10	150	2.31	3.45
6	152	6.61	168	10	150	3.33	4.97

* Other sizes, length, pressure ratings and colors are available on request