

PL OFFSHORE FUEL SD HOSE

Hose for Petroleum Products

Anti-Static Fuel, Oil And Liquid Mud Suction

Offshore Platform Fuel, Oil And Liquid Mud Transfer



APPLICATIONS

- Fuel, oil and liquid mud transfer from supply vessels to offshore platforms. Also suitable for sea water pumping and barite transfer.

TUBE

- Smooth black conductive NBR.

REINFORCEMENT

- High tensile textile cords with embedded steel helix wire.

COVER

- Smooth black conductive CR – abrasion, ozone, and hydrocarbon resistant. Flame retardant.

COLOUR

- Black with orange spiral stripe.

TEMPERATURE RANGE

- 30°C (-22°F) to +70°C (+158°F)

SAFETY FACTOR

- 3 : 1

I.DØ		O.DØ		Working Pressure		BR	Vacuum	Weight	
Inch	mm	Inch	mm	Bar	PSI	mm	Bar	lbs/ft	kg/m
1	25	1.45	39	17	255	115	0.9	0.70	1.05
2	51	2.60	66.5	17	255	245	0.9	1.38	2.05
3	76	3.70	94	17	255	390	0.9	2.34	3.49
4	102	4.80	120.5	17	255	555	0.9	3.40	5.06
5	127	5.85	151	17	255	730	0.9	5.27	7.85
6	152	7.09	181	17	255	910	0.9	8.11	12.07
8	203	9.33	237	17	255	1340	0.9	15.11	22.49

* Other sizes, length, pressure ratings and colours are available on request