



## PW150

## Non Oily Food Transfer Hose



### APPLICATIONS

Mandrel built food quality softwall hose for conveying of potable water, wine, vinegar, juice, soft drinks and other non oily foodstuffs.

### TUBE

Smooth white food quality synthetic rubber that meets FDA and European requirement standards.

### COVER

Smooth long lasting wrapped finish synthetic rubber that is weather resistant.

### REINFORCEMENTS

High strength synthetic cords.

### SIZES

1" - 4"

### TEMPERATURE RANGE

-31°F to 158°F (-35°C to 70°C)

### WORKING PRESSURE

150 PSI/ 10 BAR

### SAFETY FACTOR

4:1

### COLOURS

Blue

### REMARKS

- Not recommended for oily or fatty food.
- Also available: **PWH150** (Suction), **FFH150** (Fatty Food Suction).
- Product specifications may vary for other available models.



Code No.	I.D Ø		O.D Ø		Bend Radius		Working Pressure		Approx. Weight		Standard Length	
	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(psi)	(bar)	(lbs/ft)	(kg/m)	(ft)	(m)
PW150-0100-0060	1.00	25.0	1.34	34	N/A	N/A	150	10	0.36	0.54	200	60
PW150-0150-0060	1.50	38.0	1.97	50	N/A	N/A	150	10	0.76	1.13	200	60
PW150-0200-0060	2.00	51.0	2.56	65	N/A	N/A	150	10	1.27	1.90	200	60
PW150-0300-0060	3.00	76.0	3.66	93	N/A	N/A	150	10	2.21	3.30	200	60
PW150-0400-0060	4.00	102.0	4.84	123	N/A	N/A	150	10	3.82	5.70	200	60

### ACCESSORIES



Din Safety Clamp



Camlocks



Male Ends



Flange Ends



Tri Clamps Fittings



SMS Fittings



Din Fittings



RJT Fittings



Wormdrive Clips



Heavy Duty Clamps



Double Bolt Clamps

Other diameters and lengths available on request, please contact our sales office for pricing and minimums. Values indicated here are approximate figures based on 2' straight lengths of hose at 20 °C. Data subject to change without notice. The proper use and maintenance of hoses is the sole responsibility of the purchaser and ultimate user of the product.