



## PWH150

### Potable Water & Food Suction Hose



#### APPLICATIONS

Mandrel built food quality hardwall hose for conveying of potable water, wine, vinegar, juice, soft drinks and other foodstuffs.

#### TUBE

Smooth white food quality synthetic rubber that meets FDA and European requirement standards

#### COVER

Smooth long lasting wrapped finish synthetic rubber that is weather resistant.

#### REINFORCEMENT

High strength synthetic cord and helix wire.

#### SIZES

3/4" - 4"

#### TEMPERATURE RANGE

-31°F to 158°F (-35°C to 70°C)

#### WORKING PRESSURE

150 PSI/10 BAR

#### SAFETY FACTOR

4:1

#### COLOURS

Blue

#### REMARKS

- Not recommended for oily or fatty foods
- Also available: PW150 (Discharge), FFH150 (Fatty Food Suction).
- Available in 300 psi model
- Product specifications may vary for other available models



Code No.	I.D Ø		O.D Ø		Bend Radius		Working Pressure		Vacuum		Weight		Standard Length	
	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(psi)	(bar)	(psi)	(bar)	(lbs/ft)	(kg/m)	(ft)	(m)
PWH150-0075-0060	0.75	19.0	1.30	33	3.38	86	150	10	13.05	0.9	0.58	0.87	200	60
PWH150-0100-0060	1.00	25.0	1.50	38	4.45	113	150	10	13.05	0.9	0.66	0.99	200	60
PWH150-0150-0060	1.50	38.0	1.97	50	6.73	171	150	10	13.05	0.9	0.95	1.42	200	60
PWH150-0200-0060	2.00	51.0	2.56	65	9.05	230	150	10	13.05	0.9	1.45	2.16	200	60
PWH150-0250-0060	2.50	63.5	3.19	81	11.26	286	150	10	13.05	0.9	1.83	2.73	200	60
PWH150-0300-0060	3.00	76.0	3.66	93	13.46	342	150	10	13.05	0.9	2.48	3.70	200	60
PWH150-0400-0060	4.00	102.0	4.84	123	18.11	460	150	10	13.05	0.9	4.02	6.00	200	60

#### RELATED PRODUCTS



DIN Safety Clamp



Camlocks



Male Ends



Flange Ends



Tri Clamps Fittings



SMS Fittings



DIN Fittings



RJT Fittings

Other diameters and lengths available on request, please contact our sales office for pricing and minimums. Values indicated here are approximate figures based on 2' straight lengths of hose at 20 °C. Data subject to change without notice. The proper use and maintenance of hoses is the sole responsibility of the purchaser and ultimate user of the product.