



SD



APPLICATIONS

Ideal for moving large volume of air in portable or permanent ventilation or exhaust systems and utility blowers.

CONSTRUCTION

Single-ply yellow neoprene coated polyester fabric hose reinforced with a spring steel wire helix.

SIZES (inch)

4" - 24" (customable to 60")

TEMPERATURE RANGE

-65°F to 250°F (-54°C to 121°C)

Neoprene Coated Polyester Blower Hose

FEATURES

- Great compressibility
- Retractable allows for convenient storage
- Portable even at full extended length
- Listed as UL94V-0 flame retardant
- Shown with optional cuff

COLOURS

Yellow



Code No.	I.D Ø		Bend Radius		Comp. Ratio	Working Pressure		Negative Pressure		Approx. Weight		Standard Length	
	(inch)	(mm)	(inch)	(mm)		(psi)	(bar)	(psi)	(bar)	(lbs/ft)	(kg/m)	(ft)	(m)
SD-0400-25	4.00	101.60	3.00	76.20	5:1	5.40	0.40	N/A	N/A	0.25	0.37	25.00	7.62
SD-0600-25	6.00	152.40	3.50	88.90	12:1	3.00	0.20	N/A	N/A	0.30	0.45	25.00	7.62
SD-0800-25	8.00	203.20	5.00	127.00	12:1	3.00	0.20	N/A	N/A	0.40	0.60	25.00	7.62
SD-1000-25	10.00	254.00	6.50	165.10	12:1	2.50	0.20	N/A	N/A	0.60	0.89	25.00	7.62
SD-1200-25	12.00	304.80	7.50	190.50	12:1	2.00	0.10	N/A	N/A	0.70	1.04	25.00	7.62
SD-1400-25	14.00	355.60	8.50	215.90	12:1	1.70	0.10	N/A	N/A	0.80	1.19	25.00	7.62
SD-1600-25	16.00	406.40	9.50	241.30	12:1	1.50	0.10	N/A	N/A	0.90	1.34	25.00	7.62
SD-1800-25	18.00	457.20	10.50	266.7	12:1	1.30	0.10	N/A	N/A	1.00	1.49	25.00	7.62
SD-2000-25	20.00	508.00	12.00	304.80	12:1	1.10	0.10	N/A	N/A	1.10	1.64	25.00	7.62
SD-2400-25	24.00	609.60	13.00	330.20	12:1	1.00	0.10	N/A	N/A	1.60	2.38	25.00	7.62

ACCESSORIES



Other diameters and lengths available on request, please contact our sales office for pricing and minimums. Values indicated here are approximate figures based on 2' straight lengths of hose at 20 °C. Data subject to change without notice. The proper use and maintenance of hoses is the sole responsibility of the purchaser and ultimate user of the product.