



MGV

PVC Vacuum Hose



APPLICATIONS

Ideal for air, fumes and light dusts, light shavings, debris and powder applications. Suitable for: Cab Ventilation, Circuit Board Cooling, Flight Simulators, Pet & Animal Grooming Equipment, Printing, Race Car Helmet Ventilation, Residential Vacuum Cleaners, Stretch Hose, Ventilation

CONSTRUCTION

Grey PVC hose reinforced with a vinyl coated spring steel wire helix.

FEATURES

- Light weight and flexible
- Compressible with a compression ratio of 1.6:1
- Good chemical resistance
- Popular choice for floor care industry and general industrial vacuum applications
- Cuffs available

COLOURS

Grey

REMARKS

- Other colours available on request
- Also available: **MGS** (Stretch version) consult sales team for pricings and minimums



SIZES

3/4" - 2"

TEMPERATURE RANGE

-10°F to 160°F (-23.3°C to 71°C)

Code No.	I.D Ø		Bend Radius		Comp. Ratio	Working Pressure		Negative Pressure		Approx. Weight		Standard Length	
	(inch)	(mm)	(inch)	(mm)	(x:1)	(psi)	(bar)	(psi)	(bar)	(lbs/ft)	(kg/m)	(ft)	(m)
MGV-0075-50	0.75	19.05	0.88	22.4	1.6:1	15.00	1.03	14.24	0.98	0.11	0.16	50.00	15.24
MGV-0100-50	1.00	25.40	1.00	25.4	1.6:1	15.00	1.03	14.24	0.98	0.15	0.22	50.00	15.24
MGV-0125-50	1.25	31.75	1.25	31.8	1.6:1	15.00	1.03	14.24	0.98	0.18	0.27	50.00	15.24
MGV-0150-50	1.50	38.10	1.63	41.4	1.6:1	15.00	1.03	14.24	0.98	0.23	0.34	50.00	15.24
MGV-0200-50	2.00	50.80	2.30	58.4	1.6:1	15.00	1.03	14.24	0.98	0.35	0.52	50.00	15.24

ACCESSORIES



Grey Screw Cuff

Sold in standard length only. Other diameters and lengths available on request, please contact our sales office for pricing and minimums. Values indicated here are approximate figures based on 2' straight lengths of hose at 20 °C. Data subject to change without notice. The proper use and maintenance of hoses is the sole responsibility of the purchaser and ultimate user of the product.