



FLEXLOK® 600

Fiberglass Exhaust Hose



APPLICATIONS

Ideal for fume and exhaust extraction, suitable for: Aircraft, Diesel/Engine Exhaust, Exhaust Systems, Flame Retardant, Garage Exhaust and Vehicle Exhaust Systems.

CONSTRUCTION

Double plies silver construction silicone coated fiberglass fabric hose with a silver heat-resistant fiberglass liner mechanically crimped in a continuous process.

SIZES

4" - 12" (101.6mm - 304.8mm)

TEMPERATURE RANGE

-65°F to 600°F (-54°C to 315.5°C)

FEATURES

- Fabric is locked around a coated steel wire by a metal strip formed into a clip

- Metal strip acts as a wearstrip and offers outstanding external abrasion resistance
- Extremely flexible and compressible
- Fiberglass liner increases tensile strength for a longer life cycle
- Manufactured with flame retardant materials
- Ideal for medium temperature fume control and vehicle exhaust applications
- Available with a non-marking thermoplastic rubber clip cover to protect the helix and the equipment that is attached to the hose
- Negative pressure fan system with ambient air inlet recommended to maximize effectiveness and life of duct

COLOURS

Black with silver clamp

REMARKS

N/A



Code No.	I.D Ø		Bend Radius		Comp. Ratio (x:1)	Working Pressure		Negative Pressure		Approx. Weight		Standard Length	
	(inch)	(mm)	(inch)	(mm)		(psi)	(bar)	(psi)	(bar)	(lbs/ft)	(kg/m)	(ft)	(m)
FLOK600-0400-25	4.00	101.6	3.00	76.20	5:1	13.60	0.94	3.54	0.24	0.85	1.26	25.00	7.62
FLOK600-0500-25	5.00	127.0	3.50	88.90	6:1	11.00	0.76	3.00	0.21	0.95	1.41	25.00	7.62
FLOK600-0600-25	6.00	152.4	4.50	114.30	6:1	9.20	0.63	2.46	0.17	1.00	1.49	25.00	7.62
FLOK600-0800-25	8.00	203.2	5.00	127.00	6:1	8.50	0.59	1.96	0.14	1.10	1.64	25.00	7.62
FLOK600-1000-25	10.00	254.0	5.50	139.70	6:1	8.00	0.55	1.72	0.12	1.20	1.79	25.00	7.62
FLOK600-1200-25	12.00	304.8	6.00	152.40	6:1	7.30	0.50	1.62	0.11	1.50	2.23	25.00	7.62

ACCESSORIES



Clip Cover Protect



Steel Flanges



Bridge Clamps



Branches



Connectors



J Locks



Latch Locks



Pin Locks



Reducers



Ts



Transitions



Ys

Other diameters and lengths available on request, please contact our sales office for pricing and minimums. Values indicated here are approximate figures based on 2' straight lengths of hose at 20 °C. Data subject to change without notice. The proper use and maintenance of hoses is the sole responsibility of the purchaser and ultimate user of the product.