

FLEXLOK® 750

Diesel Exhaust Hose



APPLICATIONS

Ideal for high temperature diesel exhaust or reel and drop systems. Suitable for: Diesel/ Engine Exhaust, Dynamometer Testing, Exhaust Systems, Fume Exhaust, Glass Drying, High Temperature, Paper Mills and Vehicle Exhaust Systems.

CONSTRUCTION

Double plies red wire inserted fiberglass fabric hose with a silver heat-resistant fiberglass liner mechanically crimped in a continuous process.

SIZES

3" - 12" (76.2mm - 304.8mm)

TEMPERATURE RANGE

-40°F to 750°F (-40°C to 400°C)

FEATURES

- Fabric is locked around a coated steel wire by a metal strip formed into a clip
- Metal strip acts as a wearstrip and offers outstanding external abrasion resistance
- Excellent heat stability
- Good flexibility, durability and flow characteristics
- Inserted wire fabric and fiberglass liner increases tensile strength for a longer life cycle

COLOURS

Red


REMARKS

N/A



Code No.	I.D Ø		Bend Radius		Comp. Ratio	Working Pressure		Negative Pressure		Approx. Weight		Standard Length	
	(inch)	(mm)	(inch)	(mm)		(psi)	(bar)	(psi)	(bar)	(lbs/ft)	(kg/m)	(ft)	(m)
FLOK750-0300-25	3.00	76.2	3.00	76.20	3:1	16.00	1.10	4.91	0.34	0.80	1.19	25.00	7.62
FLOK750-0400-25	4.00	101.6	3.50	88.90	3:1	15.00	1.03	4.42	0.30	1.00	1.49	25.00	7.62
FLOK750-0500-25	5.00	127.0	4.00	101.60	5:1	13.50	0.93	3.93	0.27	0.90	1.34	25.00	7.62
FLOK750-0600-25	6.00	152.4	5.00	127.00	5:1	12.00	0.83	3.44	0.24	1.10	1.64	25.00	7.62
FLOK750-0800-25	8.00	203.2	7.00	177.80	5:1	10.00	0.69	1.96	0.14	1.70	2.53	25.00	7.62
FLOK750-1000-25	10.00	254.0	9.00	228.60	5:1	9.50	0.66	1.72	0.12	2.00	2.98	25.00	7.62
FLOK750-1200-25	12.00	304.8	11.00	279.40	5:1	8.00	0.55	1.47	0.10	2.30	3.42	25.00	7.62

ACCESSORIES



Steel Flanges




Bridge Clamps



Branches



Connectors



J Locks



Latch Locks



Pin Locks



Reducers



Ts



Transitions



Ys

Other diameters and lengths available on request, please contact our sales office for pricing and minimums. Values indicated here are approximate figures based on 2' straight lengths of hose at 20 °C. Data subject to change without notice. The proper use and maintenance of hoses is the sole responsibility of the purchaser and ultimate user of the product.