



BACCO FF

HD Foodgrade PVC Hose



APPLICATIONS

Great performance beverage hose. Ideal for liquids, wines, spirits and liquor with an alcohol content of up to 20%.

CONSTRUCTION

Hose made with plasticized vinyl compound with spiral, smooth inside.

SIZES

0.79"-5.00" (20mm-127mm)

TEMPERATURE RANGE

14°F to 140°F (-10°C to 60°C)

FEATURES

- Heavy duty
- Light and flexible
- Smooth interior for optimal flow

- Phthalates free
- Chemical and weather resistant
- Does not impart taste or colours to conveying products
- Hydrolysis resistant
- Food grade outer wear strip
- Wear strip provides additional wear and tear resistance
- Food grade according to EU Regulation n° 10/2011 (classes A, B, C and dry food)

COLOURS

Transparent with red plastic spiral

REMARKS

- Antistatic version is available upon request.



Code No.	I.D Ø		Min. Wall Thickness		Max. Wall Thickness		Bend Radius		Vol.	Vacuum		Working Pressure		Burst Pressure		Appx. Wt	Std. Lt
	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)		(psi)	(bar)	(psi)	(bar)	(psi)	(bar)	(kg/m)	(m)
BACCO-0020-0050	0.79	20.0	0.13	3.2	0.14	3.5	4.33	110.0	0.07	14.22	0.98	130.53	9	391.60	27	0.31	50
BACCO-0025-0050	0.98	25.0	0.13	3.3	0.15	3.7	6.69	170.0	0.09	14.22	0.98	116.03	8	348.09	24	0.40	50
BACCO-0030-0050	1.18	30.0	0.14	3.5	0.15	3.9	7.48	190.0	0.12	14.22	0.98	116.03	8	348.09	24	0.50	50
BACCO-0032-0050	1.25	31.8	0.14	3.5	0.15	3.9	9.06	230.0	0.14	14.22	0.98	101.53	7	304.58	21	0.52	50
BACCO-0038-0050	1.50	38.1	0.16	4.1	0.18	4.5	10.24	260.0	0.19	14.22	0.98	101.53	7	304.58	21	0.73	50
BACCO-0040-0050	1.57	40.0	0.16	4.1	0.18	4.6	10.63	270.0	0.21	14.22	0.98	101.53	7	304.58	21	0.76	50
BACCO-0045-0050	1.77	45.0	0.17	4.4	0.19	4.9	12.20	310.0	0.24	14.22	0.98	101.53	7	304.58	21	0.92	50
BACCO-0050-0050	1.97	50.0	0.19	4.7	0.21	5.3	13.78	350.0	0.31	14.22	0.98	87.02	6	261.07	18	1.10	50
BACCO-0051-0050	2.00	50.8	0.19	4.7	0.21	5.3	13.78	350.0	0.32	14.22	0.98	87.02	6	261.07	18	1.12	50
BACCO-0060-0050	2.36	60.0	0.20	5.2	0.23	5.8	16.34	415.0	0.47	14.22	0.98	87.02	6	261.07	18	1.47	50
BACCO-0063-0050	2.50	63.5	0.22	5.5	0.24	6.1	17.32	440.0	0.51	14.22	0.98	87.02	6	261.07	18	1.63	50
BACCO-0070-0050	2.76	70.0	0.22	5.6	0.25	6.3	18.90	480.0	0.61	14.22	0.98	72.52	5	217.56	15	1.80	50
BACCO-0076-0050	3.00	76.2	0.22	5.7	0.25	6.3	20.67	525.0	0.66	14.22	0.98	72.52	5	217.56	15	1.96	50
BACCO-0080-0050	3.15	80.0	0.24	6.1	0.27	6.8	21.85	555.0	0.55	14.22	0.98	72.52	5	217.56	15	2.20	30
BACCO-0090-0050	3.54	90.0	0.25	6.4	0.28	7.1	24.80	630.0	0.63	14.22	0.98	72.52	5	217.56	15	2.61	30
BACCO-0100-0050	3.94	100.0	0.29	7.3	0.32	8.1	27.36	695.0	0.78	12.80	0.88	72.52	5	217.56	15	3.31	30
BACCO-0102-0050	4.02	102.0	0.29	7.3	0.32	8.1	27.36	695.0	0.80	12.80	0.88	72.52	5	217.56	15	3.36	30
BACCO-0120-0050	4.72	120.0	0.31	7.8	0.34	8.6	35.43	900.0	1.16	12.80	0.88	58.02	4	174.05	12	4.21	30
BACCO-0127-0050	5.00	127.0	0.30	7.7	0.34	8.6	39.37	1000.0	1.25	12.80	0.88	58.02	4	174.05	12	4.41	30

ACCESSORIES



Din Safety Clamp



Camlocks



Male Ends



Flange Ends



Tri Clamps Fittings



SMS Fittings



Din Fittings



RJT Fittings

Cont..



BACCO FF

HD Foodgrade PVC Hose



APPLICATIONS

Great performance beverage hose. Ideal for liquids, wines, spirits and liquor with an alcohol content of up to 20%.

CONSTRUCTION

Hose made with plasticized vinyl compound with spiral, smooth inside.

SIZES

0.79"-5.00" (20mm-127mm)

TEMPERATURE RANGE

14°F to 140°F (-10°C to 60°C)

FEATURES

- Heavy duty
- Light and flexible
- Smooth interior for optimal flow

- Phthalates free
- Chemical and weather resistant
- Does not impart taste or colours to conveying products
- Hydrolysis resistant
- Food grade outer wear strip
- Wear strip provides additional wear and tear resistance
- Food grade according to EU Regulation n° 10/2011 (classes A, B, C and dry food)

COLOURS

Transparent with red plastic spiral

REMARKS

- Antistatic version is available upon request.



ACCESSORIES



Wormdrive
Clips



Heavy Duty
Clamps



Double Bolt
Clamps

Other diameters and lengths available on request, please contact our sales office for pricing and minimums. Values indicated here are approximate figures based on 2' straight lengths of hose at 20 °C. Data subject to change without notice. The proper use and maintenance of hoses is the sole responsibility of the purchaser and ultimate user of the product.