



MARTE A.O.

Colour: blue

Temperature range: from - 10°C to + 60°C (14F / 140F)

Features: hose in special antimigration PVC compound reinforced with an antishock rigid PVC spiral, it's resistant to abrasion, ageing, atmospheric agents and ozone.

APPLICATIONS:

for suction and delivery of mineral oil, lubricants, crude oils (naphta and diesel oil).

TECHNICAL DATA:

Part number	Inside Ø	Min. wall thickness	Max. wall thickness	Weight	Working press.	Bursting press.	Vacuum	Bending radius	Roll length	Volume
	mm	mm	mm	g/m	bar	bar	mH2O	mm	m	m³
MT 01 020.0 000.0	20	4,0	4,2	420	8	24	10	140	50	0,074
MT 01 025.0 000.0	25	4,3	4,6	550	8	24	10	170	50	0,098
MT 01 032.0 000.0	31,8	4,4	4,7	700	8	24	10	205	50	0,145
MT 01 038.0 000.0	38,1	4,4	4,7	810	7	21	10	235	50	0,193
MT 01 040.0 000.0	40	4,3	4,7	830	7	21	10	250	50	0.222
MT 01 050.0 000.0	50	4,9	5,3	1150	6	18	10	300	50	0,326
MT 01 052.0 000.0	50,8	4,9	5,3	1170	6	18	10	300	50	0,330
MT 01 063.0 000.0	63.5	5.6	6	1690	6	18	10	370	50	0.511
MT 01 076.0 000.0	76,2	5,8	6,3	2060	5	15	10	440	50	0,676
MT 01 080.0 000.0*	80	5,9	6,6	2210	5	15	10	460	30	0,548
MT 01 102.0 000.0*	102	7,1	7,9	3370	4	12	9	600	30	0,795

* For min. run only further sizes available on request

Other sizes are available on request

