



AW300



APPLICATIONS

Heavy duty softwall hose for compressed air, water and non aggressive fluids for various industries.

CONSTRUCTION

Synthetic polymers compound with high strength yarn reinforcements.

SIZES

1/4" to 1" (6mm to 25mm)

TEMPERATURE RANGE

-40°F to 176°F (-40°C to 80°C)

Premium Air and Water Hose, 300 PSI

FEATURES

- Smooth interior
- Abrasion resistant
- Ageing and weather resistant

COLOURS

- Black

SAFETY FACTOR

4:1

REMARKS

- Not suitable for solvents or gas.



CODE	I.D Ø		O.D Ø	WORK PRESS.		BURST PRESS.		APPROX. WEIGHT	LENGTH
	(inch)	(mm)	(mm)	(psi)	(bar)	(psi)	(bar)	(kg/m)	(m)
KA-006	1/4	6	12	300	20	1200	80	0.108	100
KA-008	5/16	8	14	300	20	1200	80	0.132	100
KA-010	3/8	9.5	16.5	300	20	1200	80	0.182	100
KA-013	1/2	13	20	300	20	1200	80	0.231	100
KA-016	5/8	16	23	300	20	1200	80	0.273	100
KA-019	3/4	19	28	300	20	1200	80	0.423	100
KA-025	1	25	36	300	20	1200	80	0.671	100

ACCESSORIES



Quick Connect Couplings



Male Hose Barb, NPT/BSP



Universal Claw Couplings