



WAH JOO SENG



PVC/PU
HOSES



DIAMOND CLEAR

Clear PVC Braided Hose



APPLICATIONS

Ideal for delivery of industrial liquids, light chemicals, gases, reducing agents, diluted acids and alkalis.

CONSTRUCTION

Constructed with layers of PVC and top quality polyester thread reinforcements.

SIZES

1/4" to 1" (6mm to 25mm)

TEMPERATURE RANGE

23°F to 149°F (-5°C to 65°C)

FEATURES

- Low maintenance
- No added paraffins
- Resistant to most chemicals

- Pressure withstanding
- Crystal clear visibility
- Flexible
- Smooth Interior

SAFETY FACTOR

3:1

COLOURS

- Clear

REMARKS

- Not suitable for solvents and gas



CODE	I.D Ø		O.D Ø	WORK PRESS. (@ AMBIENT)		BURST PRESS.		APPROX. WEIGHT	LENGTH
	(inch)	(mm)	(mm)	(psi)	(bar)	(psi)	(bar)	(kg/m)	(m)
DC-006	1/4	6	11	145	10	435	30	0.10	100
DC-010	3/8	10	15	130	9	392	27	0.14	100
DC-013	1/2	13	18	130	9	392	27	0.17	100
DC-016	5/8	16	22	116	8	348	24	0.25	100
DC-019	3/4	19	26	87	6	261	18	0.35	100
DC-025	1	25	32	72	5	250	15	0.42	100
DC-038	1-1/2	38	47	72	5	250	15	0.80	40
DC-050	2	50	59	72	5	250	15	0.93	40

ACCESSORIES



Camlock Couplings



Claw Couplings



Quick Connect Couplings



Hose Barb, NPT/ BSP



KC Nipple



Hose Clips

Pressure values are based on straight lengths of hose tested at ambient temperature. All specifications are *subject to change without notice*.

Flexibility Fits

www.wahjooseng.com

kingflex@wahjooseng.com

+65 6298 3211