



GP150

Air and Water Delivery, Black, 10 bar

APPLICATIONS

Lightweight general purpose softwall air and water hose for use in plants, constructions and mines.

TEMPERATURE RANGE

-31°F to 158°F (-35°C to 70°C),

WORKING PRESSURE

150 psi/ 10 bar

SAFETY FACTOR

4:1

COLOURS

Black with Yellow Spiral Stripe

REMARKS

• Also available: **GP300** (Air and Water Hose, 20 bar, Code A3).



TUBE

Oil mist resistant, smooth black synthetic rubber compound

REINFORCEMENT

High strength synthetic cord piles

COVER

Smooth wrapped weather resistant synthetic rubber

SIZES

1/2" to 12"



Code No.	I.D Ø		OD Ø		Working Pressure		Approx. Weight	
	(inch)	(mm)	(inch)	(mm)	(psi)	(bar)	(lbs/ft)	(kg/m)
A1013	1/2	13	0.79	20	150	10	0.18	0.25
A1019	3/4	19	1.02	26	150	10	0.26	0.38
A1025	1	25	1.38	35	150	10	0.40	0.61
A1032	1-1/4	32	1.77	45	150	10	0.69	1.03
A1038	1-1/2	38	2.05	52	150	10	0.87	1.30
A1051	2	51	2.56	65	150	10	1.14	1.70
A1057	2-1/4	57	2.71	69	150	10	1.53	2.29
A1063	2-1/2	63.5	2.99	76	150	10	1.64	2.45
A1076	3	76	2.62	92	150	10	1.81	2.70
A1090	3-1/2	90	4.13	105	150	10	1.94	2.90
A1102	4	102	4.56	116	150	10	2.08	3.10
A1114	4-1/2	114	5.19	132	150	10	3.06	4.57
A1127	5	127	5.78	147	150	10	3.99	5.95
A1152	6	152	6.77	172	150	10	4.41	6.58
A1203	8	203	8.54	217	150	10	3.95	5.89
A1254	10	254	10.59	269	150	10	5.09	7.60
A1305	12	305	12.76	324	150	10	7.71	11.51

ACCESSORIES



Camlocks



Male Ends



Flange Ends

Values indicated here are approximate figures based on 0.5m straight lengths of hose tested at 20 °C. Data subject to change without notice.