

**GP300**

Air and Water Delivery, Green, 20 bar

APPLICATIONS

Strong and flexible medium duty softwall hose designed for air and water applications at 20 bar.

TEMPERATURE RANGE

-31°F to 158°F (-35°C to 70°C),

WORKING PRESSURE

300 psi/ 20 bar

SAFETY FACTOR

4:1

COLOURS

Green with Yellow Spiral Stripe

REMARKS

• Also available: **GP150** (Air and Water Hose, 10 bar, Code A1).

**TUBE**

Oil mist resistant, smooth SBR/NBR compound

REINFORCEMENT

High strength synthetic cord piles

COVER

Smooth wrapped weather resistant synthetic rubber

SIZES

3/4" to 4"



Code No.	I.D Ø		OD Ø		Working Pressure		Approx. Weight	
	(inch)	(mm)	(inch)	(mm)	(psi)	(bar)	(lbs/ft)	(kg/m)
A3019	3/4	19	1.22	31	300	20	0.45	0.67
A3025	1	25	1.46	37	300	20	0.56	0.84
A3032	1-1/4	32	1.93	49	300	20	1.04	1.55
A3038	1-1/2	38	2.13	54	300	20	1.11	1.65
A3051	2	51	2.60	66	300	20	1.35	2.02
A3063	2-1/2	63.5	3.13	79.5	300	20	1.82	2.71
A3076	3	76	3.62	92	300	20	2.13	3.18
A3102	4	102	4.72	120	300	20	2.61	3.90

ACCESSORIES

Camlocks



Male Ends



Flange Ends

Values indicated here are approximate figures based on 0.5m straight lengths of hose tested at 20 °C. Data subject to change without notice.