

**HP YELLOW RIBBED COVER****High Pressure Yellow Air Hose****APPLICATIONS**

Ideal for delivery of high pressure air, water and light chemical solution spray, compressed air, agriculture, vineyard, lawn and pest control industries.

CONSTRUCTION

PVC with double braided high grade synthetic yarns.

SIZES

1/4" to 1" (6.5mm to 25mm)

TEMPERATURE RANGE

-4°F to 140°F, max. 176°F (short term)

-20°C to 60°C, max. 80°C (short term)

FEATURES

- Ribbed cover to reduced drag and increased flexibility
- High pressure

- Smooth interior
- Chemical resistant
- Weatherproof
- Flexible and lightweight
- Non-kink
- Conforms to ISO 1401 / 2398

COLOURS

- Yellow

SAFETY FACTOR

4:1

REMARKS

- Not suitable for solvents or gas.
- Made in Korea.



CODE	I.D Ø		O.D Ø	WORK PRESS		BURST PRESS.		APPROX. WEIGHT	LENGTH
	(inch)	(mm)	(mm)	(psi)	(bar)	(psi)	(bar)	(kg/m)	(m)
CY-006	1/4	6.5	12.1	600	40	2400	160	0.11	100
CY-008	5/16	8	14	600	40	2400	160	0.13	100
CY-010	3/8	10	16	600	40	2400	160	0.17	100
CY-013	1/2	13	20	600	40	2400	160	0.23	100
CY-019	3/4	19	27	300	20	1200	80	0.19	100
CY-025	1	25	34	300	20	1200	80	0.27	100

ACCESSORIES

Quick Connect Couplings



Male Hose Barb, NPT/BSP



Universal Claw Couplings

Values indicated are approximate figures based on straight length of hose tested at ambient temperature.