

**PS150**

Oil/Fuel Delivery Hose, 10 bar

APPLICATIONS

Softwall hose use for delivery of petroleum products with aromatic contents up to 30%.

TUBE

Smooth black nitrile compound

REINFORCEMENT

High strength synthetic cords with anti-static copper wire,

COVER

Smooth long lasting wrapped finish in high grade chloroprene rubber, weather resistant

SIZES

1" to 6"

TEMPERATURE RANGE

+5°F to 158°F (-15°C to 70°C),

WORKING PRESSURE

150 psi/ 10 bar

SAFETY FACTOR

4:1

COLOURS

Black with Red Spiral

REMARKS

• Also available: **PH150** (Oil Suction Hose, Code P1).



Code No.	I.D Ø		OD Ø		Working Pressure		Approx. Weight	
	(inch)	(mm)	(inch)	(mm)	(psi)	(bar)	(lbs/ft)	(kg/m)
P7025	1	25	1.42	36	150	10	0.46	0.69
P7032	1-1/4	32	1.65	42	150	10	0.64	0.96
P7038	1-1/2	38	2.05	52	150	10	0.86	1.29
P7051	2	51	2.52	64	150	10	0.96	1.43
P7063	2-1/2	63.5	3.11	79.5	150	10	1.47	2.19
P7076	3	76	3.54	90	150	10	1.49	2.23
P7090	3-1/2	90	4.13	105	150	10	1.93	2.88
P7102	4	102	4.65	118	150	10	2.31	3.45
P7152	6	152	6.61	168	150	10	3.33	4.97

ACCESSORIES

Camlocks



Male Ends



Flange Ends



Hammer Unions

Kamvalok® and
EpsilonDry Disconnect
CouplingsBreakaway
Couplings

Values indicated here are approximate figures based on 0.5m straight lengths of hose tested at 20 °C. Data subject to change without notice.