



SUPER STEAM HOSE

Steel Braided Steam Hose



APPLICATIONS

Designed for saturated hot steam.

TUBE

Black, smooth, EPDM rubber, resistant to saturated steam

REINFORCEMENT

Piles of steel wire cords

COVER

Black, pin pricked, smooth (wrapped finish), EPDM rubber with excellent resistance to high temperatures, weathering, abrasion and ageing

SIZES

1/2" to 3"

TEMPERATURE RANGE

-40°F to 410°F (-40°C to 210°C),
450°F (232°C) peaks

WORKING PRESSURE

270 psi (18 bar)

SAFETY FACTOR

10:1

COLOURS

Red

REMARKS

- Hose is not recommended for steam cleaner.
- Drain after use to prolong product lifespan.
- Using hose at 232°C decreases product lifespan.



Code No.	I.D Ø		OD Ø		Working Pressure		Approx. Weight	
	(inch)	(mm)	(inch)	(mm)	(psi)	(bar)	(lbs/ft)	(kg/m)
S1013	1/2	13	1.02	26	270	18	0.25	0.37
S1016	5/8	16	1.10	28	270	18	0.34	0.50
S1019	3/4	19	1.26	32	270	18	0.39	0.58
S1025	1	25	1.50	38	270	18	0.44	0.66
S1032	1-1/4	32	1.81	46	270	18	0.59	0.88
S1038	1-1/2	38	2.13	54	270	18	0.87	1.29
S1051	2	51	2.64	67	270	18	1.53	2.28
S1063	2-1/2	63.5	3.31	84	270	18	2.25	3.33
S1076	3	76	3.86	98	270	18	2.92	4.34

ACCESSORIES



Ground Joint
Couplings



Bolt Clamps

Values indicated here are approximate figures based on 0.5m straight lengths of hose tested at 20 °C. Data subject to change without notice.