KINGFLEX
Hoses & Couplings

TPE/EPDM, Non-kink Multi Colour Utility Hose

UH300

APPLICATIONS
- Utility hose for water, air, nitrogen with different colours for easy identification

COVER
- Cross-linked EPDM compound resistant to weather, abrasion and most chemicals

TUBE
- Smooth interior, cross-linked EPDM compound

REINFORCEMENT
- Piles of high strength polyester threads

FEATURE
- Extremely lightweight for easy handling and non-kink good for tight space restraint

COLOUR
- Black, Blue, Red, Yellow, other colours on request*

TEMPERATURE
- -20°C to 90°C

SAFETY FACTOR
- 3 : 1

Please contact our office for steam services and non-interchangeable end fittings suitable for dedicated lines.

I.D ⌀		O.D ⌀		Working Pressure		Bursting Pressure		Weight	
inch	mm	inch	mm	bar	psi	bar	psi	lbs/ft	kg/m
3/4	19	1.26	32	20	300	60	900	0.33	0.49
1	25	1.46	37	20	300	60	900	0.38	0.56

* minimun roll quantity applies for special colours

QUALITY INDUSTRIAL RUBBER HOSES KINGFLEX

WAH JOO SENG www.wahjooseng.com +65 6298 3211